

Liebherr 63K 6 ton mobil byggkran

Maxlyft 6 ton
Kranarmens längd 43 m
Max lyfthöjd 32,7 m
(vid jibbning 53 m)

Stödben:
Bredd: 4,50 m
Längd: 5,50 m



Lyftkapacitet

Liebherr 63K

Utligg (m)	11,0	12,0	14,0	16,0	18,0	20,0	22,0	24,0	26,0	28,0	30,0	32,0	34,0	35,0	37,0	38,0	39,0	40,0	41,0	42,0	43,0	
Bomlängd (m)																						
43	6,00	5,73	4,70	3,96	3,41	3,00	2,65	2,38	2,16	1,95	1,80	1,64	1,51	1,46	1,35	1,30	1,26	1,22	1,17	1,14	1,10	
40	6,00	6,00	4,97	4,19	3,62	3,17	2,81	2,53	2,30	2,10	1,90	1,75	1,61	1,55	1,44	1,39	1,34	1,30				
35	6,00	6,00	5,37	4,54	3,92	3,44	3,05	2,76	2,51	2,26	2,10	1,90	1,76	1,70								
30	6,00	6,00	5,80	4,90	4,24	3,72	3,31	2,95	2,69	2,35	2,25											

- Radiostyrd
- Elanslutning: 380 V/63 Amp

Kranens längd: 15,6 m
 Chassits längd: 12,6 m
 Chassits höjd: 4,45 m
 Chassits bredd: 2,5 m
 Stödben i längd: 5,5 m
 Stödbenens bredd: 4,5 m
 Motviktens svängradie: 3,6 m

