

Terex CTT 561

32 ton fast byggkran




Maxlyft 32 ton

Kranarm längd:	84 m	84 m
Max lyfthöjd:	72 m	73 m
Stödben:		injektering
Längd:	8,0 m	2,3 m
Bredd:	8,0 m	2,3 m



Lyftkapacitet

Terex CTT 561

			m	19	24	29	34	39	44	49	54	59	64	69	74	79	84
16t		17,66	m	13,65	10,25	8,07	6,56	5,64	4,74	4,03	3,46	2,99	2,60	2,26	1,97	1,72	1,50
	32t	10,02	m	13,13	9,74	7,54	6,00	5,06	4,14	3,42	2,83	2,34	1,94	1,59	1,29	1,03	0,80
16t		20,79	m	16,00	12,74	10,15	8,35	7,26	6,19	5,35	4,67	4,11	3,64	3,24	2,90	2,60	
	32t	11,80	m	16,58	12,49	9,84	7,99	6,86	5,75	4,87	4,17	3,58	3,09	2,67	2,31	2,00	
16t		24,58	m	16,00	15,67	12,57	10,42	9,11	7,84	6,83	6,02	5,35	4,79	4,31	3,90		
	32t	13,72	m	20,27	15,43	12,30	10,11	8,78	7,46	6,43	5,59	4,90	4,32	3,83	3,40		
16t		27,96	m	16,00	16,00	14,71	12,23	10,73	9,26	8,10	7,16	6,39	5,75	5,20			
	32t	15,32	m	23,31	17,86	14,34	11,87	10,37	8,89	7,73	6,79	6,01	5,36	4,80			
16t		30,24	m	16,00	16,00	16,00	13,45	11,82	10,22	8,96	7,94	7,10	6,40				
	32t	16,54	m	25,59	19,68	15,85	13,17	11,54	9,94	8,68	7,65	6,81	6,10				
16t		32,17	m	16,00	16,00	16,00	14,49	12,74	11,03	9,68	8,60	7,70					
	32t	17,70	m	27,75	21,38	17,25	14,36	12,61	10,88	9,51	8,41	7,50					
16t		36,02	m	16,00	16,00	16,00	16,00	14,58	12,65	11,13	9,90						
	32t	19,53	m	31,14	24,04	19,45	16,23	14,27	12,35	10,83	9,60						
16t		36,48	m	16,00	16,00	16,00	16,00	14,80	12,84	11,30							
	32t	19,63	m	31,32	24,19	19,56	16,33	14,36	12,43	10,90							
16t		37,74	m	16,00	16,00	16,00	16,00	15,40									
	32t	20,11	m	32,00	24,89	20,14	16,82	14,80									

- Radiostyrd
- Elanslutning: 400 V/250 Amp

